



GPL 12880

12V 88.0Ah

GPL 12880 is a general purpose battery with 10 years expected life under normal float charge. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.




Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	88Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	Approx. 30kg(66.1 lbs)
Maximum Discharge Current	700A(5sec)
Internal Resistance	Approx. 6mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging	26.4A
Current Limit	
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
Self Discharge	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Thread Insert & Bolt
Container Material	-Polypropylene (UL94-HB)*Flammability resistance of UL94-V0 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

Dimensions



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	381.00	525.00	183.00	109.00	62.60	36.40	25.20	19.60	16.90	11.00	9.10	4.92
1.67V	348.10	231.70	178.10	106.90	61.62	35.77	24.78	19.46	16.76	10.86	9.01	4.87
1.70V	334.00	223.00	176.00	106.00	61.20	35.50	24.60	19.40	16.70	10.80	8.97	4.85
1.75V	296.00	205.00	166.50	100.50	59.45	34.95	24.15	19.05	16.40	10.60	8.93	4.82
1.80V	258.00	187.00	157.00	95.00	57.70	34.40	23.70	18.70	16.10	10.40	8.88	4.79
1.83V	220.00	169.00	147.50	89.50	55.95	33.85	23.25	18.35	15.810	10.20	8.84	4.76

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	4,010.00	2,774.00	2,020.00	1,250.00	731.00	426.00	297.00	231.00	1989.00	131.00	111.00	62.50
1.67V	3,730.00	2,558.40	1,957.00	1,222.00	721.20	421.00	292.80	228.90	197.60	130.30	110.30	62.15
1.70V	3,610.00	2,446.00	1,930.00	1,210.00	717.00	420.00	291.00	228.00	197.00	130.00	110.00	62.00
1.75V	3,240.00	2,273.00	1,860.00	1,155.00	698.50	413.50	286.50	224.50	194.00	128.00	108.50	60.90
1.80V	2,870.00	2,080.00	1,790.00	1,110.00	680.00	407.00	282.00	221.00	191.00	126.00	107.00	59.80
1.83V	2,500.00	1,887.00	1,720.00	1,045.00	661.50	400.50	277.50	217.50	188.00	124.00	105.50	58.70

• All mentioned values are average values.


Trickle (or Float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use



Terminal Voltage (V) and Discharge Time (25°C 77°F)



Battery Voltage and Charge Time for Cycle Use



Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C > (A)	0.2C < (A) < 0.5C	0.5C < (A) < 1.0C	(A) > 1.0C

Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40-2.50	0.3C
Standby	25°C (77°F)	2.275	2.25-2.30	

Sales Office URL: WWW.CSB-BATTERY.COM

CSB BATTERY CO., LTD.
TAIWAN OFFICE
 Tel: +886-2-8751-5000
 Fax: +886-2-8751-6161
 E-mail: service@csb-battery.com.tw

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHANGHAI OFFICE
 Tel: +86-21-5046-1622, 5046-0833
 Fax: +86-21-5064-3314

CSB BATTERY TECHNOLOGIES, INC
USA OFFICE
 Tel: +1-817-244-7777/1-8003 CSBUSA(272872)
 Fax: +1-817-244-4445
 E-mail: csb@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
BEIJING OFFICE
 Tel: +86-10-6597-8060, 6597-8070
 Fax: +86-10-6597-8050
 E-mail: chinastls@csb-battery.com

CSB BATTERY OF NETHERLANDS B.V
NETHERLANDS OFFICE
 Tel: +31(0) 180 418 140
 Fax: +31(0) 180 418 327
 E-mail: eurosales@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHENZHEN OFFICE
 Tel: +86-755-88316356 88316488 88316396
 Fax: +86-755-88316548
 E-mail: she@csb-battery.com